IBERRY®

ACF5 ARAÇ TUTUCU
Kullanım Kılavuzu

Parçaların Tanıtımı



Manyetik Halka



Type-C Kablo



Havalandırma Kancası



Vantuzlu Taban



④ Kanca Kilitleme Düğmesi
⑤ Kanca Sabitleme Desteği
⑥ Kilitleme Kancası
⑦ Havalandırma Desteği
⑩ Döner Bilye Kilit Vidası
⑪ Destek Kolu Açı Vidası
⑫ Destek Kolu Tabanı

Telefonun Yerleştirilmesi

Bu tutucuyu kullanmadan önce telefon kılıfınıza manyetik halka takmanız gerekip gerekmediğini kontrol edin.

▸ **Standart Telefon Kılıfı**

Manyetik halkayı kılıfın arka yüzüne yapıştırın



▸ **MagSafe Telefon Kılıfı**

Birlikte verilen manyetik halkayı takmadan doğrudan kullanın



- ❗ MagSafe manyetik halkası takılmamış standart bir telefon kılıfıyla telefonu tutucuya yerleştiremezsiniz.
- ❗ Manyetik halka kullanmadan önce ürünün yapıştırma talimatlarını mutlaka okuyun.
- ❗ MagSafe kılıf kullanıyorsanız ayrıca manyetik halka takmanız gerekmez. iPhone 12 sonrası tüm iPhone modelleri, kılıfsız kullanıldıklarında manyetik halka olmadan doğrudan tutucuya takılabilir.
- ❗ Telefonu yerleştirmeden önce manyetik çekim gücünün sürüşteki titreşimler nedeniyle düşmeyi önleyecek kadar güçlü olduğundan emin olun.

Kablosuz Şarj

■ Güç Bağlantısı

Şarj cihazını ve tutucuyu verilen Type-C USB kablosuyla bağlayın.

❗ Bağlayacağınız şarj cihazını aşağıdaki teknik özelliklere göre seçtiğinizden emin olun.

- **Standart Kablosuz Şarj**
  : 5 V / 2,0 A veya üzeri
- Hızlı Kablosuz Şarj
  : QC 3.0 vb., 9 V çıkış veya üzeri

Belirtilen özellikleri karşılamayan bir şarj cihazı kullanırsanız ürün doğru çalışmayabilir. Aracın USB bağlantı noktasını kullanırken çıkış kapasitesini kontrol edin.



■ Qi2 Hızlı Kablosuz Şarj Rehberi

Bu ürün, yalnızca Qi2 kablosuz şarjı destekleyen akıllı telefonlarda 15 W hızlı kablosuz şarjı destekler.

iPhone	iPhone 15 serisi ve sonrası
Galaxy	Galaxy S25 serisi ve sonrası (MagSafe kılıf veya halka gerekir)

■ Telefonu Yerleştirme ve Kablosuz Şarj

1. Ürüne güç verildiğinde durum LED'i ③ yanar; rengi beyazdır.
2. Telefonun ortasını tutucunun önündeki ① işaretli daireye hizaladığınızda telefon manyetik olarak tutucuya bağlanır ve şarj işlemi başlar.

❗ Kablosuz şarj düzgün çalışmıyorsa veya şarj hızı belirgin ölçüde düşükse aşağıdaki kontrolleri yapın.

A. Standart telefon kılıfına takılan MagSafe halka doğru konumlandırılmamışsa:

➡ Manyetik halkanın telefon kılıfının tam ortasına doğru şekilde yerleştirildiğini kontrol edin.

B. Bağlı USB güç kaynağının çıkış kapasitesi (adaptör veya araç USB girişi) yetersizse:

➡ Ürünü yukarıdaki özellikleri karşılayan bir USB şarj cihazına bağlayın.

C. Ürün doğrudan güneş ışığı veya klima çıkışından gelen sıcak hava nedeniyle aşırı ısınırsa:

➡ Telefonun ve tutucunun yeterince soğuması için kablosuz şarjı bir süre durdurun.

LED Gösterge Bilgileri

Durum LED'i aşağıdaki biçimde yanar:

Güç Açık	Beyaz
Şarj Oluyor	Mavi (telefon tutucuya takılıyken)
Şarj Hatası	Beyaz ve mavi LED dönüşümlü yanar

Şarj Hataları (Koruma Devresinin Devreye Girmesi)
Aşırı gerilim ve akım, düşük gerilim ve akım, aşırı ısınma, metal algılama, şarj konumu hataları vb.

Kurulum

Havalandırma Kancası Kurulumu

‣ Havalandırma Kancasını Takma

1. Kanca kilitleme düğmesini tamamen gevşetin ④ ve kilitleme kancasını ⑥ iyice içeri itin.

❗ Havalandırma sabitleme kancası yalnızca genişliği 10–31 mm olan ızgara kanatlarına takılabilir.





2. Kilitleme kancasını ⑥ orta havalandırma kanadına takın; sabitleme desteği ⑤ üç kanada sıkıca dayanmalıdır. Desteği ızgaraya sıkıca bastırın; kanatları elinizle düz tutarken kilitleme düğmesini sıkarak ④ kancayı sabitleyin.

❗ Izgara kanatları düz değilken veya aşırı kuvvet uygulayarak kilitleme somununu sıkmayın; kanatlar zarar görebilir. Dikkatli olun.





❗ Havalandırma çıkışına monte etmeden önce yandaki çizimi inceleyin ve havalandırma ızgarasının şeklinin montaja uygun olduğundan emin olun.

Montaja uygun	
Montaja uygun değil	

‣ Tutucunun Montajı

1. Önce sabitleme somununu ② döner bilyeden geçirin, ardından bilyeyi yuvasına sıkıca itin. Açıyı ayarlayıp sabitleme somununu sıkın ② ve tutucuyu sabitleyin.





Vantuzlu Taban Kurulumu

‣ Montaj Seçeneğini Belirleyin



Yüksek Açı

Sağlam ve dengeli montaj için kısa katlanır; titreşimi azaltır.



Alçak Açı

Sürüş sırasında ön görüşü engellememek amacıyla daha alçak konumda takılır.

‣ Vantuzlu Tabanı Takma

1. Tutucunun yüksekliğini ve uzaklığını dikkate alarak montaj yerini dikkatlice seçin. Vantuzun sağlam tutunması için önce vantuz destek plakasını ⑫ takın; ardından vantuzu üzerine yerleştirin.

   ❗ Vantuzu çok eğimli yüzeylere veya sallanabilen ya da deforme olabilen malzemelere takmayın.



2. Vantuzu doğrudan yüzeye veya destek plakasını çift taraflı bantla yapıştırmadan önce yüzeyi verilen alkollü mendille silerek toz ve yağdan arındırın.

   ❗ Destek plakasını yapıştırdıysanız çift taraflı bandın tamamen tutunması için vantuzu yaklaşık 2 saat takmayın.

   ❗ Jel ped uzun süreli kullanımdan sonra yapışkanlığını kaybederse suyla durulayıp tamamen kurumasını bekleyin.

3. Jel pedin şeffaf koruyucu filmini çıkarın.



4. Vantuz mandalını dik ⑨ konuma kaldırın. Vantuzu yüzeye sıkıca bastırarak hava boşluğu kalmasını önleyin; sabitlemek için mandalı indirin.



‣ Tutucunun Montajı

1. Döner bilye sabitleme somununu ② döner bilyeden geçirin.
2. Döner bilyeyi yuvasına takın, tutucuyu istediğiniz açıya ayarlayın ve sabitleme somununu sıkın ② ve tutucuyu sabitleyin.





‣ Destek Kolu Açısının Ayarlanması

1. Destek kolu açı vidasını gevşetin ⑪ ve döner bilye kilit vidasını ⑩, destek kolunu ve tutucuyu istediğiniz konuma getirdikten sonra hareket etmemeleri için vidaları iyice sıkın.

   ❗ Döner bilye uzun kullanımdan sonra gevşerse döner bilye kilit vidasını ⑩ bozuk para veya tornavidayla sıkın.



2. Tutucunun konumu çok yüksek veya alçaksa destek kolunu ters yönde yeniden takarak ⑧ konumu değiştirebilirsiniz; aşağıdaki çizime bakın.



⚠ Uyarılar

1. Telefon kılıfınızda manyetik kart varken ürünü kullanmayın.
2. Bu üründe güçlü mıknatıs bulunur. Elektronik tıbbi cihazlarla temas etmesine izin vermeyin.
3. Telefonun yerinden çıkmaması için aşırı kuvvet uygulamayın.
4. Sürüş sırasında oluşan titreşim, havalandırma ızgarası ile montaj parçaları arasında boşluk oluşturabilir. Tutucunun sabit ve sarsıntısız olduğunu düzenli kontrol edin.
5. Vantuzun tutuş gücü azaldığında ürünün düşmesini önlemek için bağlantıları ve vantuzun tutuşunu düzenli kontrol edin.
6. Vantuzun yapışkan jel pedi uzun kullanımda montaj yüzeyinde iz bırakabilir. Bu izler nötr deterjanla temizlenebilir ve zamanla kendiliğinden kaybolur.
7. USB girişine veya bağlantı ucuna yabancı madde girmesine izin vermeyin.
8. Bu ürün, duvar tipi şarj cihazına bağlanarak iç mekânda da kullanılabilir.

IBERRY®

ACF5 CAR HOLDER

User's Manual

Names of Each Part



Magnetic Ring



Type-C Cable



Air Vent Hook



Suction Base



- ④ Hook locking knob
- ⑤ Hook Fixing Support
- ⑥ Locking hook
- ⑦ Air vent Support
- ⑩ Rotating Ball Locking Bolt
- ⑪ Stay Angle Fixing Bolt
- ⑫ Stay Support Stand

Phone Mounting

Before using this holder, please check if you need to attach a magnetic ring to your phone case.

▸ Regular Phone Case

Attach a magnetic ring to the back of the case



▸ MagSafe Phone Case

Use directly without attaching the included magnetic ring



- ❗ You cannot mount your phone to holder with a regular phone case that does not have the MagSafe magnetic ring attached.
- ❗ When using a magnetic ring, be sure to read the attachment instructions for that product before attaching it.
- ❗ If you use a MagSafe phone case, you do not need to attach a magnetic ring, and all iPhone models after the iPhone 12 can be used directly with the holder without a magnetic ring if you do not use a case.
- ❗ Before mounting , make sure the magnet-force is strong enough to prevent the phone from falling due to vibrations during driving.

Wireless Charging

■ Power Connection

Connect the charger and stand using the included Type-C USB cable.

❗ Be sure to select the charger you want to connect by referring to the following specifications.

- General Wireless Charging
  : 5V/2.0A or Higher
- Fast Wireless Charging
  : QC 3.0, etc. 9V output or higher

If you use a charger that does not meet the specifications, the device may not operate properly, and when connecting to a vehicle's USB port, be sure to check the port capacity.



■ Qi2 Fast Wireless Charging Guide

This product supports 15W fast wireless charging only for smartphones that support Qi2 wireless charging.

iPhone	iPhone 15 series and later
Galaxy	Galaxy S25 series and late (MagSafe case or ring attachment required)

■ Phone Mounting & Wireless Charging

1. When power is supplied to the product, the signal LED③ lights up in White color.
2. When you place the center of the phone against the circle ① marked on the front of the mount, the phone automatically attaches to the holder and charging begins.

! If wireless charging does not function properly or the charging speed is significantly slow, please refer to the following information.

A. If the MagSafe ring attached to a standard phone case is not positioned correctly

➡ Please check that the magnetic ring is correctly attached to the center of the phone case.

B. If the output capacity of the connected USB power source (charger or vehicle USB port) is insufficient

➡ Please connect the device to a USB charger that meets the above specifications.

C. If the device becomes excessively hot due to direct sunlight or hot air from an air conditioner

➡ Please stop wireless charging for a period of time to allow the phone and the mount to cool down sufficiently.

LED Indicator Information

The signal LED lamp indicator lights up as follows:

Power On	White
Charging	Blue (When phone is placed on the stand)
Charging Error	White and Blue LED cross lighting

Charging Errors (Protection Circuit Operation)
Over-Voltage and Over-Current, Low-Voltage and Low-Current, Over-Heating, Metal Detection, Charging Position Errors, ETC

Installation

Vent Hook Installation Instructions

‣ Vent Hook Installation

1. Fully loosen the hook locking knob④ and push the locking hook⑥ all the way in.

! The air vent fixing hook can only be installed on vent blades with a width of 10–31 mm.





2. Hook the locking hook⑥ onto the center vent blade so that the fixing support⑤ rests firmly against three vent blades. After fully pressing the fixing support against the vent blades, hold the vent blades level by hand and tighten the locking knob④ to secure the hook.

! Do not tighten the locking cap with excessive force or while the vent blades are not level, as this may damage the vent blades.
Please exercise caution.





! If installed at the air conditioning port, Please refer to the image next to it first,Confirm in advance whether the grid shape of the air conditioning port can be installed.

Can be installed	
Can not install	

‣ Holder Assembly

1. First, pass the fixing cap ② over the rotating ball, then firmly push the ball into the mount. Adjust to the desired angle and tighten the fixing cap ② to secure it.





Suction Base Installation Instructions

‣ Select Installation Option



High Angle

Folded short for a firm, stable installation with minimal vibration



Low Angle

Installed at a lower angle to avoid obstructing the driver's forward view during driving

‣ Suction Base Installation

1. Select the mounting position carefully, taking into account the height and distance of the holder. To securely fix the suction pad, be sure to attach the suction support plate⑫ first, then install the suction pad on top of it.

   ❗ Do not install the suction pad on heavily curved surfaces or materials that are prone to shaking or deformation.



2. When attaching the suction pad directly to the surface or securing the support plate with double-sided tape, be sure to thoroughly clean the surface with the included alcohol pad to remove any dust or oil.

   ❗ If the support plate has been attached, do not put on the suction base for approximately 2 hours to allow the double-sided tape to fully adhere.

   ❗ If the gel pad loses its adhesion after long-term use, rinse it with water and let it dry completely to recover its stickiness.

3. Remove the protective film (clear) from the gel pad.



4. Lift the suction lever⑨ to a vertical position. While firmly pressing the suction base against the surface to prevent any gaps or air leakage, push the lever down to secure the suction.



- **Holder Assembly**

1. Pass the rotation fixing cap② through the rotation ball.
2. Insert rotating ball into the socket, then adjust the holder to the desired angle and tighten the fixing cap② to secure it.



Insert the cap into the ball



Tighten the fixing cap to desired direction and angle

- **Stay Angle Adjustment**

1. Loosen the stay angle fixing bolt⑪ and the rotating ball locking bolt⑩, adjust the stay angle and holder position as desired, then tighten them firmly to prevent any movement.

   ❗ If the rotating ball becomes loose after prolonged use, tighten the rotating ball locking bolt⑩ using a coin or a screwdriver.



2. If the mount position is too high or too low, you can adjust the position by reinstalling the stay⑧ in the opposite direction, as shown in the illustration below.



⚠ Caution

1. Do not use the product while a magnetic card is inserted in your phone case.
2. This product contains a strong magnet. Do not allow it to come into contact with electronic medical devices.
3. To prevent the phone from detaching, do not apply excessive force.
4. Due to vibration while driving, gaps may form between the air vent and the mounting components. Check regularly to ensure the holder is securely fixed and not shaking.
5. To prevent the product from falling due to reduced suction strength of the suction cup, please regularly check the fixing and suction condition.
6. The adhesive gel pad attached to the suction cup may leave marks on the mounting surface after prolonged use. These marks can be removed with a neutral detergent, and they will naturally disappear over time.
7. Make sure no foreign substances enter the USB port or connector.
8. This product is also designed for indoor use by connecting it to a wall charger.